

Performance

Evap(°F)/Cond(°F)	<u>45 / 130</u>	<u>45 / 100</u>
RG(°F)/SubCool(°F)	<u>65 / 15</u>	<u>65 / 15</u>
Capacity (Btu/hr)	78600	94500
Power (Watts):	6950	4720
Current (Amps):	12.85	10.25
EER (Btu/Wh):	11.40	20.00
Mass Flow (lbs/hr):	1140	1175
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-avg))	3.0 Avg	4.5 Max
Record Date:	2007-12-06	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	7.76
Bore Size(in):	0.00	Displ(ft ³ /hr):	781.18
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	18.75	Mounting Height (in):	19.50 *
Suction Size (in):	1 1/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	81		
Initial Oil Charge (oz):	85		
Net Weight (lbs):	126		
Internal Free Volume (in ³):	639.0		
Horse Power:	8		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			