

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/SubCool(°F)	65 / 15	65 / 15
Capacity (Btu/hr)	103000	124500
Power (Watts):	8950	6170
Current (Amps):	16.00	12.45
EER (Btu/Wh):	11.60	20.20
Mass Flow (lbs/hr):	1500	1545
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-))	3.0 Avg	4.5 Max
Record Date:	2007-12-06	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	10.20
Bore Size(in):	0.00	Displ(ft ³ /hr):	1026.88
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.00	Mounting Height (in):	21.75 *
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	110		
Net Weight (lbs):	135		
Internal Free Volume (in ³):	809.0		
Horse Power:	10		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			