



Product Code

6570/21A

Ball Valve Access Port
2"5/8ODS

CLASSIC

Impiego

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1:

- HCFC (R22)
- HFC (R134a, R404A, R407C, R410A, or R507)
- HFO and HFO/HFC blends (R1234ze, R448A, R449A, R450A, R452A, R513A)

Maximum allowable pressure PS = 45 bar.

Allowable temperatures TS = -40 / +150 °C

Dettagli prodotto

Connections ODS Ø [in.] 2.5/8"

Connections ODS Ø [mm]

Ball port Ø [mm] 60

Kv[m³/h] 380

PS[bar] 45

TS[°C] min. -40

TS[°C] max. +150

Package pcs 1

Note dove espressamente riportate

(1): MWP = 500 psi for 6570/.. and 6590/.. - MWP = 435 psi for 6571/.. and 6591/.. according to UL approval

(2): not UL approved

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

Valves 6590/.. running out of stock